

HIGH-PERFORMANCE LITHIUM GREASE



UPDATED: 5/10/2021

PART#	NET WT.	UPC	CASE QTY.
16-LG	11oz/311g	0-32167-99008-5	12
Low-Friction Lubrication and Heavy-Duty Protection			

DESCRIPTION:

B'laster White Lithium Grease is low-odor, clean, white grease that lubricates by creating a protective barrier. It protects against moisture and oxidation and is safe for a wide range of applications. It provides low-friction lubrication and heavy-duty protection.

B'LAST ON:

Auto Hinges & Latches, Hitches & Receivers, Gears.
Also good for: Hoists & Winches, Forklifts, Bearings, Sprockets, Pulleys, Chains, Bushings, Slides & Ways, Rollers, Hinges

DIRECTIONS FOR USE:

Shake the can well before using. Spray liberally to surfaces. Don't be shy, spray more if needed. It is suggested that the can be at room temperature when dispensing.

SAFETY:

DANGER! EXTREMELY FLAMMABLE: Do not spray near sparks, heat or open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone.

Exposure Symptoms:

Inhalation: Remove person to fresh air and keep comfortable for breathing. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention. Call a POISON CENTER/doctor if you feel unwell.

Skin Contact: Not normally required. If skin irritation occurs: Get medical advice/attention.

Eye Contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion: Unlikely to be required but if necessary treat symptomatically. Do not give anything by mouth to an unconscious person. Seek medical treatment.

TYPICAL PROPERTIES:

- Flash Point:** -155°F (-104°C)
- Density (20°C):** 5.8 lbs/gal
- Specific Gravity (20°C):** 0.7
- Boiling Point:** Not Applicable
- Product Category:** Multi-Purpose Lubricant
- Body Shop Safe:** Yes
- Base Type:** Lithium
- Appearance:** Almond
- Spray Pattern:** Conical (Cone-Shaped)
- Odor:** Fuel Oil-like
- Temperature Range:** -20 to 140°F
- VOC:** < 10%
- Clean-Procedures:** Start by scraping or wiping off excess product. Product can be removed with hot water and dish washing detergent. Use standard prep solvent to remove product prior to painting.